



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1  
The article number refers to powder-coated version.

At loose-flange connection  $\varnothing E$   
mounting-length B 25mm longer

Pipe	Article-no.	$\varnothing c$	$\varnothing C$	$\varnothing e$	$\varnothing E$	A	B	S	Weight in kg
100-80-80	11101275	100	115	77	92	40	130	1,5	0,85
120-100-100	11121275	120	135	100	115	50	150	1,5	1,25
140-100-100	11141275	136	151	100	115	50	150	1,5	1,25
150-100-100	11151276	150	165	100	115	50	170	1,5	1,40
150-120-120	11151275	150	165	120	135	50	170	1,5	1,65
175-120-120	11171276	175	190	120	135	50	200	1,5	2,00
200-140-140	11201276	200	215	136	151	60	200	1,5	2,35
200-150-150	11201275	200	215	150	165	60	200	1,5	2,50
224-150-150	11221275	220	235	150	165	60	220	1,5	2,65
250-200-200	11251275	250	265	200	215	60	250	1,5	3,50
300-224-224	11301276	300	315	220	235	70	300	1,5	4,80
350-250-250	11351275	350	365	250	265	70	300	1,5	5,30
400-300-300	11401275	399	414	300	315	70	350	1,5	6,20
450-350-350	11451275	449	464	350	365	80	400	1,5	9,20
500-400-400	11501275	499	514	399	414	80	450	1,5	11,40

Denomination:

**Conical symmetrical forks 60°**

Date: 11/14

Datasheet-no. 5/7

Rev. 0