



Pipe diameter tolerance and roundness tolerance to DIN EN 10296-1
The article number refers to powder-coated version

electr. rotary drive 230V AC / 24V DC,
Operating-time approx. 15 s < Ø300,
24 s > Ø300 with 4 adjustable
limit-switches 5A / 250V.

| Pipe | Ø 60 | Ø 80 | Ø 100 | Ø 120 | Ø 140 | Ø 150 | Ø 175 | Ø 200 |
|--------------|----------|----------|----------|----------|----------|----------|----------|----------|
| Article-no. | - | 57720807 | 57721007 | 57721207 | 57721407 | 57721507 | 57721707 | 57722007 |
| Ø d | - | 77 | 99 | 119 | 135 | 149 | 174 | 199 |
| Ø D | - | 92 | 115 | 135 | 151 | 165 | 190 | 215 |
| A | - | 257 | 268 | 278 | 286 | 293 | 306 | 318 |
| B | - | 83 | 93 | 103 | 111 | 116 | 131 | 143 |
| L | - | 100 | 100 | 120 | 140 | 150 | 175 | 200 |
| S | - | 1,5 | 2 | 2 | 2 | 2 | 2 | 2 |
| Weight in kg | - | 3,40 | 3,70 | 4,10 | 4,50 | 4,80 | 5,40 | 6,20 |
| Pipe | Ø 224 | Ø 250 | Ø 280 | Ø 300 | Ø 315 | Ø 350 | Ø 400 | Ø |
| Article-no. | 57722207 | 57722507 | 57722807 | 57723007 | 57723107 | 57723507 | 57724007 | - |
| Ø d | 219 | 249 | 276 | 299 | 311 | 349 | 398 | - |
| Ø D | 235 | 265 | 292 | 315 | 327 | 365 | 414 | - |
| A | 328 | 343 | 357 | 368 | 386 | 405 | 430 | - |
| B | 153 | 168 | 182 | 193 | 220 | 239 | 264 | - |
| L | 200 | 200 | 200 | 200 | 200 | 200 | 200 | - |
| S | 2 | 2 | 2 | 2 | 2 | 2 | 2 | - |
| Weight in kg | 6,60 | 7,30 | 8,00 | 8,60 | 11,60 | 13,00 | 15,00 | - |

In case of placing your order please state the desired signal-current.
Please take notice of the following no.-code.
The 2-digit number has to be added to 8-digit article-no. code.

| Make | Signal-current |
|-------------------------------------|----------------|
|73 AIR TORQUE Adjustable drive | 230V, AC |
|74 AIR TORQUE Adjustable drive | 24V, AC/DC |

Denomination:
**Throttle-/ Shut-off valves with seal,
electrically operated with adjustable drive**

| | |
|---------------|-------|
| Date: | 06/15 |
| Datasheet-no. | 8/8 |
| Rev. | 0 |